

### MIRAPAKON™ surface preparation – Food & Beverage Industry

#### COMPANY IDENTIFICATION

##### **MIRAPAKON™**

2500, Boul. du Parc-Technologique  
Quebec (QC) G1P 4S6  
CANADA

TEL: (418) 874-0054 #255

HOURS: Monday-Friday 8:00 à 17:00 (EAST)

[www.mirapakon.com](http://www.mirapakon.com)

##### **PRODUCT DESCRIPTION**

The **MIRAPAKON WP100** is an alcohol based washing product.

**This product can be used as a degreaser, a surface cleaner and a drying agent for the preparation of surfaces prior to treatment with MIRAPAKON MK300.**

It is contraindicated to use the product during working hours in a room where food is being process

This product is not compatible with all touchscreens.

##### **FEATURES**

- Alcohol based liquid
- Remove grease and other organic contaminants
- Fast drying.
- Remove water from the surface

##### **APPLICATION TEMPERATURE**

Apply at room temperature. It's possible, under certain conditions, to apply on a surface under 32°F (4°C)

##### **CURING SCHEDULE**

Allow the surface to dry before the application of **MIRAPAKON MK300**

##### **USE**

Use as a surface preparation prior to treatment with MIRAPAKON MK300:

##### **MIXING AND THINNING**

This system is ready to use and requires no mixing. The product should not be thinned.

##### **APPLICATION METHOD**

Cover all production equipment.

##### **CLEANUP AND SAFETY**

###### **Cleanup**

Use a dry cloth to absorb any excess of **MIRAPAKON WP100**. This product is soluble in water but it should never be disposed via the foul sewer.

Test **MIRAPAKON WP100** on a small area to insure compatibility with the surface before proceeding

Wet a clean cloth or a soft sponge with **MIRAPAKON WP100** and wipe the surface. Removed any excessive product from the surface with a dry cloth.

###### **Safety**

Follow all caution statements on this product data sheet and on the MSDS for this product. Employ normal workmanlike safety precautions. Wear appropriate Personnel Protective Equipment.

Make sure to remove dirt, dust, oil, wax, grease and all other contaminants before application of **MIRAPAKON MK300**.

## Respiratory Protection

Use a mask with organic vapors caption cartridges to avoid breathing alcohol vapors.

## CAUTION

### FLAMMABLE MATERIAL

– (Flash point closed cup: 54 °F)

Use in a well ventilated area.

Keep away from sparks and open flames. All electrical equipment and installations should be made and grounded in accordance with the National Electric Code. In areas where explosion hazards exist, workmen should be required to use non-ferrous tools and wear conductive and non-sparking shoes.

## HANDLING & STORAGE

Store indoors at 32°F to 100°F, at ambient Relative Humidity. Immediately close container after transferring product to application container.

Shelf life: 24 month months if sealed, partial usage and/or multiple container openings may decrease shelf life.

## Disclaimer:

Performance depends upon factors such as surface condition, application technique and application environment. Accordingly, MIRAPAKON™ warrants solely that **MIRAPAKON WP100** conforms to its product specification at the time of initial retail sale.

**MIRAPAKON™ DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE.**

In the event of a breach of warranty, MIRAPAKON™'s sole liability will be to refund the purchase price of this product or replace the product at the option of MIRAPAKON™. **IN NO EVENT SHALL MIRAPAKON™ BE LIABLE FOR INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES.**